

## Additional application for the DAMPER ZZ-R Spec DSC Plus has been confirmed for the TOYOTA LAND CRUISER 250 (TRJ250W / GDJ250W)



Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.





Front : 29mm(1.1in) Up / Rear : 8mm(0.3in) Up

Click here for price and availability

## Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
ΤΟΥΟΤΑ					
LAND CRUISER 250	2024/04-	TRJ250W	2TR-FE	98662	4959094986621
	2024/04-	GDJ250W	1GD-FTV	98062 495909498	4939094980021

## **Product Description**

• Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.

• The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.

• The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a

stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
 During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.

• Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.

• With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification				
Front	Rear			
0	0			
Coilovers	Separate			
Upright	Upright			
Reinforced Rubber	Stock			
14.0	4.5			
280	280/290			
BS	BS			
$+10 \sim +50$	$-15 \sim +20$			
	Front Coilovers Upright Reinforced Rubber 14.0 280 BS			



■ Remarks : Lift up Version. Compatible with Diesel, Gasoline. Data on ride height from TRJ250W. %Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」 %Adjustability in ride height may vary between vehicles.

Optional Parts			
Product Name	Code No.	Remarks	
DSC PLUS Vehicle Specific Set TYPE-V	15301	Upgrade to the DSC Plus with the	
DSC FLOS Venicle Specific Set TTFE-V	V 15501	vehicle specific set	
DSC PLUS GPS Sensor Kit	15214	Easily input speed	
DSC PLUS Remote Switch	15219	Separate switch to change modes	、 I ±
			ງ.,∟ບ



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
ΤΟΥΟΤΑ	LANDCRUISER250	TRJ250W	2024年6月	VX First Edition

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	2240		
	軸重(kg) (Axle Weight)	1160	1080	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	265/65 R18	265/65 R18	
	ホイールサイズ (Wheel Size)	18inch 7.5J Inset60	18inch 7.5J Inset60	
	レバー比 (Lever Ratio)	1.1	1.1	
	\ (Toe)	+0°01'	+0°21'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-0°05'	-0°03'	
	キャスター (Caster)	+3°17'	_	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)	
	スプリングレート(kgf/mm) (Spring Rate)	14.0	4.5		
	スプリング自由長(mm) (Free Length of Spring)	280	RL:280 RR:290		
	スプリング内径(mm) (Spring Inner Diameter)	φ62 - (φ97.5) - φ62	φ135 - (φ172) - φ100.5		
DAMPER ZZ-R	減衰力調整段数 (Damping force Adjustment)	1段 ~ 32段 (HARD) (SOFT)	1段 ~ 32段 (HARD) (SOFT)	DSC Plus装着時 32,64,96段へ変更可能	
仕様(Spec.)	地面〜フェンダー(mm) (Ground〜Fender)	955	957		
	基準車高(mm) (Difference from Stock)	+29	+8		
	車高調整範囲(mm) (Height Adjustment Range)	$+10 \sim +50$	$-15 \sim +20$		
	最低地上高(㎜) (Minimum Ground Clearance)	229mm (ホーシング(デフ部))			
初めてご使用される際の推奨減衰力 (Recommended Damping force)		18段	24段	左記に記載の減衰に合わせ てからご使用ください	

%Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.
%During installation turn the dial all the way to the right and then make adjustment towards the left accordingly.

## **Product Description**

Lift up version damper ZZ-R

- Increase the ride height for a more aggressive look.
- Spring rate and shock length have been revised to allow greater height adjustability.
- Even while increasing the height, vehicle stability during high speed is maintained.
- For vehicles above 80km/h increase the damping force by 4~6 clicks to improve vehicle stability.