

## Additional applications for the DAMPER ZZ-R Spec DSC Plus has been confirmed for the HONDA CIVIC RS (FL1)

## Spec DAMPER ZZ-R DS

Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.







Front : 26mm Down / Rear : 27mm Down

Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
HONDA					
CIVIC RS	2024/09-	FL1	L15C	98669	4959094986690

## Product Description

Click here for price and availability Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes

depending on variables such as road condition and number of passengers.

• The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.

• The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.

• During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.

• Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force. • With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification					
	Front	Rear			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Stock	Reinforced Rubber			
Spring Rate kgf/mm	6.0	5.0			
Free Length of Spring mm	180	200			
Spring Type 💥	BS	BS			
Ride Height Adjustability mm	-45 $\sim$ 0	-50 $\sim$ -10			



■ Remarks : Only for vehicles after minor change. (2024/09- Front Insertion Diameter Φ53.8) Unchecked with AT • HYBRID models. \*Abbreviation for Spring Types [ST:ID62 Straight Spring], [BS:Barrel or Tapered, Vehicle Specific Springs] \*Adjustability in ride height may vary between vehicles.

Optional Parts		
Product Name	Code No.	Remarks
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set
DSC PLUS GPS Sensor Kit	15214	Vehicle speed can be easily inputted
DSC PLUS Remote Switch	15219	Allows you to conveniently switch settings.



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
HONDA	CIVIC	FL1	2024年11月	RS

		フロント	リア	備考
確認車両情報		(Front)	(Rear)	(Remarks)
	車重(kg) (Vehicle Weight)	1350		
	軸重(kg) (Axle Weight)	820	530	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	235/40R18	235/40R18	
	ホイールサイズ (Wheel Size)	18inch 8.0J Inset50	18inch 8.0J Inset50	
	レバー比 (Lever Ratio)	1.0	1.2	
	⊢– (Toe)	+0°01'	+0°01'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-0°55'	-2°42'	
	キャスター (Caster)	+5°29'	_	

		フロント	リア	備考
MPER ZZ-R Spec.		(Front)	(Rear)	(Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	6.0	5.0	
	スプリング自由長(mm) (Free Length of Spring)	180	200	
	スプリング内径(mm) (Spring Inner Diameter)	Ф104.5-Ф62.5	Ф62-(Ф115)-Ф62	
DAMPER ZZ-R 仕様(Spec.)	減衰力調整段数 (Damping force Adjustment)	1段 ~ 32段 (HARD) (SOFT)	1段 ~ 32段 (HARD) (SOFT)	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground〜Fender)	653	653	
	基準車高(mm) (Difference from Stock)	-26	-27	
	車高調整範囲(mm) (Height Adjustment Range)	-45~0	-50~-10	
	最低地上高(㎜) (Minimum Ground Clearance)	106mm (アンダーパネル (アルミ製) )		
初めてご使用される際の推奨減衰力				左記に記載の減衰に合わ

初めてご使用される際の推奨減衰力	16段	16段	左記に記載の減衰に合わせ
(Recommended Damping force)			てからご使用ください

% Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest. % During installation turn the dial all the way to the right and then make adjustment towards the left accordingly

## Product Description

- New spring and shock absorber setting for vehicles after the minor change.
- Bump stroke, rebound stroke has been balanced for a more comfortable ride quality.
- ■Vehicle specific front stabilizer links are included.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Increase the damping force by 4~6 click for speeds above 80km/h to improve vehicle stability.

Enjoy customizing the CIVIC with the SFC project.

Ride comfort was the central focus in the development of the SFC suspension model. Experience the suspension with superior stability and comfort even with a lowered stance.