

## Additional application for the DAMPER ZZ-R Spec DSC Plus has been confirmed for the SUBARU CROSSTREK (GUD/GUE)

# DAMPER ZZ-R DSC+

Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.







#### Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
SUBARU					
CROSSTREK	2022/09-	GUD,GUE	FB20-MA1	98564	4959094985648

#### **Product Description**

Click here for price and availability

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification					
	Front	Rear			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Coilovers			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Reinforced Rubber			
Spring Rate kgf/mm	5.0	5.0			
Free Length of Spring mm	200	220			
Spring Type※	ST	ST			
Length Adjustment	-70 ∼ 0	-65 ∼ 0			



■ Remarks: 2WD/4WD Compatible. Data on ride height from GUE. Uncheck with Strong Hybrid model. Rear service panel must be removed or modified to install rear suspension.

\*\*Abbreviation for Spring Types \[^ST:\] ID62 Straight Spring \], \[^BS:\] Barrel or Tapered, Vehicle Specific Springs \] \*\*Adjustability in ride height may vary between vehicles.

Optional Parts					
Product Name	Code No.	Remarks			
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set			
DSC PLUS GPS Sensor Kit	15214	Easily input speed			
DSC PLUS Remote Switch	15219	Separate switch to change modes			

### DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
SUBARU	CROSSTREK	GUE	2024年9月	Limited

確認車両情報		フロント (Front)	קנו (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	1610		
車両情報 (Vehicle Information)	軸重(kg) (Axle Weight)	970	640	
	タイヤサイズ (Tire Size)	225/55 R18	225/55 R18	
	ホイールサイズ (Wheel Size)	18inch 7.0J Inset55	18inch 7.0J Inset55	
	レバー比 (Lever Ratio)	1.0	1.0	
アライメントデータ (Alignment Data)	├– (Toe)	+0°00'	+0°04'	
	キャンバー (Camber)	-1°32'	-2°57'	
	キャスター (Caster)	+6°01'	_	

DAMPER ZZ-R Spec		フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	5.0	5.0	(Herrien)
	スプリング自由長(mm) (Free Length of Spring)	200	220	
	スプリング内径(㎜) (Spring Inner Diameter)	φ62	φ62	
	減衰力調整段数	1段 ~ 32段	1段 ~ 32段	DSC Plus装着時
DAMPER ZZ-R	(Damping force Adjustment)	(HARD) (SOFT)	(HARD) (SOFT)	32,64,96段へ変更可能
仕様(Spec.)	地面〜フェンダー(mm) (Ground〜Fender)	716	722	
	基準車高(mm) (Difference from Stock)	-24	-26	
	車高調整範囲(㎜) (Height Adjustment Range)	-70 ∼ 0	-65 ∼ 0	
	最低地上高(㎜) (Minimum Ground Clearance)	154mm (マフラーフランジ)		

初めてご使用される際の推奨減衰力 (Recommended Damping force)	16段	20段	左記に記載の減衰に合わせてからで使用ください
(Recommended Bamping force)			Ch DC IX/11 (ICCV)

<sup>%</sup>Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.
%During installation turn the dial all the way to the right and then make adjustment towards the left accordingly

#### **Product Description**

- $\blacksquare$  Increase the damping force for greater stability during high speeds.
- Lower your vehicle for a stylish form.
- Make adjustments to the damping force depending on the number of passenger and road conditions.
- Decrease the riding force to improve ride quality at lower speeds and rougher road surfaces.
- Increase the damping force by 4~6 click for speeds above 80km/h to improve vehicle stability.