

Additional applications for the DAMPER ZZ-R  
has been confirmed for the NISSAN FAIRLADY Z (Z34)

DAMPER ZZ-R

Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

[Click here for further details on DAMPER ZZ-R](#)



Front : 16mm Down / Rear : 30mm Down

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
NISSAN					
FAIRLADY Z	2008/12-2022/04	Z34	VQ37VHR	92674	4959094926740

Product Description

[Click here for price and availability](#)

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

商品仕様		
	フロント	リ ア
減衰力調整	32段調整	32段調整
全長調整	○	○
ショックアブソーバー構成	コイルオーバー	別体式
正立式 or 倒立式	正立式	正立式
アッパーマウント	強化ゴム	強化ゴム
バネレート kgf/mm	10.0	10.0
スプリング自由長 mm	200	210
スプリングタイプ※	ST	BS
車高調整範囲 mm	-55 ~ 0	-60 ~ -15



■Remarks : MT/AT Compatible. NISMO Compatible. HZ34 unchecked. Rear trim must be modified.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

Optional Parts		
Product Name	Code No.	Remarks
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
NISSAN	FAIRLADY Z	Z34	2018年12月	NISMO

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重(kg) (Vehicle Weight)	1540		
	軸重(kg) (Axle Weight)	850	690	
	タイヤサイズ (Tire Size)	245/40 R19	285/35 R19	
	ホイールサイズ (Wheel Size)	19inch 9.5J Inset40	19inch 10.5J Inset23	
	レバー比 (Lever Ratio)	1.0	1.1	
アライメントデータ (Alignment Data)	トー (Toe)	+0°02'	+0°05'	
	キャンバー (Camber)	-1°19'	-3°12'	
	キャスター (Caster)	+5°15'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	10.0	10.0	
	スプリング自由長(mm) (Free Length of Spring)	200	210	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ62 - φ97	
	減衰力調整段数 (Damping force Adjustment)	1段 ~ 32段 (HARD) (SOFT)	1段 ~ 32段 (HARD) (SOFT)	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground〜Fender)	687	681	
	基準車高(mm) (Difference from Stock)	-16	-30	
	車高調整範囲(mm) (Height Adjustment Range)	-55 ~ 0	-60 ~ -15	
	最低地上高(mm) (Minimum Ground Clearance)	93mm (マフラーパイプ)		

初めてご使用される際の推奨減衰力 (Recommended Damping force)	16段	16段	左記に記載の減衰に合わせて てからご使用ください
---	-----	-----	-----------------------------

※Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.  
※During installation turn the dial all the way to the right and then make adjustment towards the left accordingly

Product Description

- ZZ-R for the Z34 has been updated to be compatible with DSC PLUS.
- Bump stroke, rebound stroke has been balanced for a more comfortable ride quality.
- Lower your vehicle for a more stylish form.
- Make adjustments to the damping force to optimize performance from the street o the circuit.
- By installing the Optional DSC PLUS vehicle specific kit, the damping force can be easily adjusted from inside the vehicle.