

Additional applications for the DAMPER ZZ-R has been confirmed for the SUZUKI JIMNY NOMADE (JC74W)

DAMPER ZZ-R

Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

[Click here for further details on DAMPER ZZ-R](#)



Front : 30mm Down / Rear : 40mm Down

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
SUZUKI					
JIMNY NOMADE	2025/04-	JC74W	K15B	92525	4959094925255

Product Description

[Click here for price and availability](#)

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Separate	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Stock	Reinforced Rubber
Spring Rate kgf/mm	2.3	2.5
Free Length of Spring mm	250	200/215
Spring Type※	BS	BS
Ride Height Adjustability mm	-60 ~ -25	-65 ~ -30



■Remarks : Front and Rear damping force dials located inside wheel well.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
SUZUKI	JIMNY NOMADE	JC74W	2025年6月	FC

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重(kg) (Vehicle Weight)	1190		
	軸重(kg) (Axle Weight)	650	540	
	タイヤサイズ (Tire Size)	195/80R15	195/80R15	
	ホイールサイズ (Wheel Size)	15inch 5.5J Inset5	15inch 5.5J Inset5	
	レバー比 (Lever Ratio)	1.0	1.0	
アライメントデータ (Alignment Data)	トー (Toe)	+0°07'	-0°01'	
	キャンバー (Camber)	+0°31'	-0°39'	
	キャスター (Caster)	+4°55'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	2.3	2.5	
	スプリング自由長(mm) (Free Length of Spring)	250	RL:200 / RR:215	
	スプリング内径(mm) (Spring Inner Diameter)	φ86.5-(φ114)-φ85	φ86.5-(φ110)-φ83	
	減衰力調整段数 (Damping force Adjustment)	1段 ~ 32段 (HARD) (SOFT)	1段 ~ 32段 (HARD) (SOFT)	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground〜Fender)	759	767	
	基準車高(mm) (Difference from Stock)	-30	-40	
	車高調整範囲(mm) (Height Adjustment Range)	-60 ~ -25	-65 ~ -30	
	最低地上高(mm) (Minimum Ground Clearance)	169mm (フロントアーム付け根)		

初めてご使用される際の推奨減衰力 (Recommended Damping force)	16段	16段	左記に記載の減衰に合わせて からご使用ください
---	-----	-----	----------------------------

※Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.  
※During installation turn the dial all the way to the right and then make adjustment towards the left accordingly.

Product Description

- Compatibility has been confirmed for the JIMNY NOMADE.
- Lower the center of gravity to limit body roll and enhance cornering performance.
- Increase the damping force for a sporty handling and lower it for a more comfortable ride quality.
- LIFT UP Model is currently being developed.