

Additional application for the DAMPER ZZ-R Lift Up version  
has been confirmed TOYOTA COROLLA CROSS HYBRID (ZVG16 / MXGH15) 4WD

DAMPER ZZ-R LIFT UP  
Model



Front : 40mm(1.6in) Up/ Rear : 27mm(1.1in) Up

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
TOYOTA					
COROLLA CROSS HYBRID	2023/10-	ZVG16	2ZR-1VM-1WM	92595	4959094925958
	2025/08-	MXGH15	M20A-1VM-1WM		

Product Description

[Click here for price and availability](#)

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	6.0	5.0
Free Length of Spring mm	220	300
Spring Type※	BS	BS
Ride Height Adjustability mm	0 ~ +50	0 ~ +40



- Remarks : 4WD Only. Metal panels above upper mount must be modified for proper installation.  
Rear damping force adjustment dials located inside wheel well. DSC PLUS recommended. Ride height data from MXGH15.

※Abbreviation for Spring Types 「ST : ID62 Straight Spring」 , 「BS : Barrel or Tapered, Vehicle Specific Springs」  
※Adjustability in ride height may vary between vehicles.

Optional Parts		
Product Name	Code No.	Remarks
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set

Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
TOYOTA	COROLLA CROSS HYBRID	MXGH15	2025年9月	GR SPORT

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重(kg) (Vehicle Weight)	1520		
	軸重(kg) (Axle Weight)	860	660	
	タイヤサイズ (Tire Size)	225/45 R19	225/45 R19	
	ホイールサイズ (Wheel Size)	19inch 7.5J Inset40	19inch 7.5J Inset40	
	レバー比 (Lever Ratio)	1.0	1.1	
アライメントデータ (Alignment Data)	トー (Toe)	+0°01'	+0°03'	
	キャンバー (Camber)	-1°14'	-0°52'	
	カスター (Caster)	+5°28'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	6.0	5.0	
	スプリング自由長(mm) (Free Length of Spring)	220	300	
	スプリング内径(mm) (Spring Inner Diameter)	φ62 - (φ115) - φ62	φ62 - (φ115) - φ62	
	減衰力調整段数 (Damping force Adjustment)	1段 ~ 32段 (HARD) (SOFT)	1段 ~ 32段 (HARD) (SOFT)	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground~Fender)	781	784	
	基準車高(mm) (Difference from Stock)	+40	+27	
	車高調整範囲(mm) (Height Adjustment Range)	0 ~ +50	0 ~ +40	
	最低地上高(mm) (Minimum Ground Clearance)	184mm (マフラーパイプ(リアメンバー下))		

初めてご使用される際の推奨減衰力 (Recommended Damping force)	24段	22段	左記に記載の減衰に合わせてからご使用ください
---	-----	-----	------------------------

※Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.  
※During installation turn the dial all the way to the right and then make adjustment towards the left accordingly.

Product Description

- Compatibility for the LIFT UP Version has been checked for 2<sup>nd</sup> generation 4WD vehicles.
- LIFT UP your vehicle for a more aggressive look.
- Spring rate and shock length have been revised to allow greater height adjustability.
- Vehicle specific short stabilizer links are included in the kit.
- Even while increasing the height, vehicle stability during high speed is maintained.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- By installing the Optional DSC PLUS vehicle specific kit, the damping force can be easily adjusted from inside the vehicle.