

Additional application for the DAMPER ZZ-R Spec DSC Plus LIFT UP Model has been confirmed for the TOYOTA COROLLA CROSS HYBRID (ZVG16 / MXGH15) 4WD





Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.







Front: 40mm(1.6in) Up/ Rear: 27mm(1.1in) Up

Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
TOYOTA					
COROLLA CROSS HYBRID	2023/10-	ZVG16	2ZR-1VM-1WM	98595	4959094985952
	HYBRID	2025/08-	MXGH15	M20A-1VM-1WM	90393

Product Description

Click here for price and availability

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification				
	Front	Rear		
Length Adjustment	0	0		
Shock Absorber Structure	Coilovers	Separate		
Upright or Inverted	Upright	Upright		
Upper Mount	Reinforced Rubber	Reinforced Rubber		
Spring Rate kgf/mm	6.0	5.0		
Free Length of Spring mm	220	300		
Spring Type※	BS	BS		
Length Adjustment	0 ~ +50	0 ~ +40		



Remarks: 4WD Only. Ride height data from MXGH15.

**Abbreviation for Spring Types 「ST: ID62 Straight Spring」, 「BS: Barrel or Tapered, Vehicle Specific Springs」 **Adjustability in ride height may vary between vehicles.

Optional Parts				
Product Name	Code No.	Remarks		
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set		
DSC PLUS GPS Sensor Kit	15214	Easily input speed		
DSC PLUS Remote Switch	15219	Separate switch to change modes		

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
TOYOTA	COROLLA CROSS HYBRID	MXGH15	2025年9月	GR SPORT

		フロント	リア	備考
確認車両情報		(Front)	(Rear)	(Remarks)
	車重(kg)	1520		
	(Vehicle Weight)			
	軸重(kg)	860	660	
	(Axle Weight)	800	000	
車両情報	タイヤサイズ	225/45 R19	225/45 R19	
(Vehicle Information)	(Tire Size)	223/43 K19	223/43 KI9	
	ホイールサイズ	19inch 7.5J Inset40	19inch 7.5J Inset40	
	(Wheel Size)	19111011 7.33 11150140	13111011 7.33 11150040	
	レバー比	1.0	1.1	
	(Lever Ratio)	1.0	1.1	
	├ ─	+0°01'	+0°03'	
	(Toe)	+0 01	+0 03	
アライメントデータ	キャンバー	-1°14'	-0°52'	
(Alignment Data)	(Camber)	-1 14	-0 32	
	キャスター	+5°28'	_	
	(Caster)	+3 20	_	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	6.0	5.0	
	スプリング自由長(mm) (Free Length of Spring)	220	300	
	スプリング内径(mm) (Spring Inner Diameter)	φ62 - (φ115) - φ62	φ62 - (φ115) - φ62	
	減衰力調整段数	1段 ~ 32段	1段 ~ 32段	DSC Plus装着時
DAMPER ZZ-R	(Damping force Adjustment)	(HARD) (SOFT)	(HARD) (SOFT)	32,64,96段へ変更可能
仕様(Spec.)	地面〜フェンダー(mm) (Ground〜Fender)	781	784	
	基準車高(mm) (Difference from Stock)	+40	+27	
	車高調整範囲(mm) (Height Adjustment Range)	0 ~ +50	0 ~ +40	
	最低地上高(㎜) (Minimum Ground Clearance)	184mm (マフラーパ	イプ(リアメンバー下))	

初めてで使用される際の推将減春力			ナシに到我のは存に合わせ
初めてご使用される際の推奨減衰力 (Recommended Damping force)	24段	22段	左記に記載の減衰に 占 れせてからご使用ください
(Recommended bumping force)			Ch JC IX/ II VCCV

[%]Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.
%During installation turn the dial all the way to the right and then make adjustment towards the left accordingly

Product Description

- ■Compatibility for the LIFT UP Version has been checked for 2nd generation 4WD vehicles.
- ■LIFT UP your vehicle for a more aggressive look.
- ■Spring rate and shock length have been revised to allow greater height adjustability.
- ■Vehicle specific short stabilizer links are included in the kit.
- ■Even while increasing the height, vehicle stability during high speed is maintained.
- ■Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- ■When riding above 80km/h increase the damping force by 4~6 clicks to improve vehicle stability.