

Additional application for the DAMPER ZZ-R Spec DSC Plus has been confirmed for the NISSAN AURA/AURA NISMO (FSNE13) 4WD

DAMPER ZZ-R DS

Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.







Front: 13mm Down / Rear: 12mm Down

Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
NISSAN					
AURA	2021/08-	FSNE13	HR12-EM47-MM48	98675	4959094986751
AURA NISMO	2024/07-	ISINLIS			

Product Description

Click here for price and availability

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification						
	Front	Rear				
Length Adjustment	0	0				
Shock Absorber Structure	Coilovers	Separate				
Upright or Inverted	Upright	Upright				
Upper Mount	Stock	Stock				
Spring Rate kgf/mm	5.0	6.0				
Free Length of Spring mm	200	200				
Spring Type※	ST	BS				
Length Adjustment	-40 ∼ 0	-20 ∼ 0				



- Remarks: 4WD Only. Rear panels must be removed or modified for proper installation. Ride height data from AURA NISMO. Unchecked with assistive vehicles.
- *Abbreviation for Spring Types 「ST: ID62 Straight Spring」, 「BS: Barrel or Tapered, Vehicle Specific Springs」 *Adjustability in ride height may vary between vehicles.

Optional Parts		
Product Name	Code No.	Remarks
DSC PLUS Vehicle Specific Set TYPE-I	15244	Upgrade to the DSC Plus with the vehicle specific set
DSC PLUS GPS Sensor Kit	15214	Easily input speed
DSC PLUS Remote Switch	15219	Separate switch to change modes

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
NISSAN	AURA NISMO	FSNE13	2024年10月	NISMO tuned e-POWE 4WD
認車両情報		フロント	IJ Ţ	備考
		(Front)	(Rear)	(Remarks)
	車重(kg)	1400		(**************************************
	(Vehicle Weight)			
	軸重(kg) (Axle Weight)	820	580	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	205/50R17	205/50R17	
	ホイールサイズ (Wheel Size)	17inch 7.0J Inset42	17inch 7.0J Inset42	
	レバー比 (Lever Ratio)	1.0	1.1	
アライメントデータ (Alignment Data)	├- (Toe)	+0°01'	+0°14'	
	キャンバー (Camber)	-1°12'	-1°46'	
	キャスター (Caster)	+6°25'	_	
		フロント	リア	備考
AMPER ZZ-R Spec.		ノロンド (Front)	(Rear)	順名 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	5.0	6.0	(2 2 2)
	スプリング自由長(mm) (Free Length of Spring)	200	200	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ62.5 - (φ120) - φ67	
DAMPER ZZ-R 仕様(Spec.)	減衰力調整段数	1段 ~ 32段	1段 ~ 32段	DSC Plus装着時
	(Damping force Adjustment) 地面〜フェンダー(mm)	(HARD) (SOFT)	(HARD) (SOFT)	32,64,96段へ変更可能
	垣圃~フェンター(IIIII) (Ground~Fender)	643	650	
	基準車高(mm) (Difference from Stock)	-13	-12	
	車高調整範囲(mm) (Height Adjustment Range)	-40 ∼ 0	-20 ∼ 0	
	最低地上高(mm) (Minimum Ground Clearance)	116mm (ボディフレームボルト頭)		
初めてご使用される際の推奨減衰力		20段	24段	左記に記載の減衰に合わt

[%]Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.
%During installation turn the dial all the way to the right and then make adjustment towards the left accordingly

Product Description

- Spring rate and shock absorber length has been optimized for 4WD vehicles.
- Front short stabilizer links are included in the kit.

(Recommended Damping force)

- Lower the center of gravity to limit body roll and enhance cornering performance.
- Bump stroke, rebound stroke has been balanced for a more comfortable ride quality.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.

てからご使用ください

■ Increase the damping force by 4~6 click for speeds above 80km/h to improve vehicle stability.